



## See nothing, hear everything

The CWM7.4 features a 150mm (6in) bass/mid-range driver set in a die-cast chassis and a Nautilus<sup>™</sup> tube loaded 25mm (1in) soft dome tweeter. With a critically formed baffle constructed from glass reinforced ABS, the speaker features a scallop under the tweeter which creates the perfect roll off for high frequencies resulting in a more accurate reproduction of sound. Utilising the best quality components, such as having Mundorf components on the crossover, combined with proven technologies such as Flowport<sup>™</sup> ensures that this speaker provides impressive sound reproduction.

## **Technical Specifications**

**Description** 2-way in-wall system

**Drive units** 1x ø25mm (1in) Nautilus<sup>™</sup> tube loaded soft dome tweeter

1x Ø150mm (6in) blue Kevlar® cone bass/midrange

Frequency Range (-6dB) 47Hz -28kHz

Recommended Amp Power 25 - 150w

Sensitivity SPL (2.83V, 1m) 89dB

Impedance Nominal (min)  $6\Omega$  ( $5\Omega$ )

415mm (16.5in) Frame height 251mm (10in) Frame width Cut-out height 395mm (15.6in) 232mm (9.1in) **Cut-out width** Reservoir box height 460mm (18.1in) 220mm (8.7in) Reservoir box width 60mm (2.4in) Reservoir box depth 90mm (3.6in) Depth behind surface 6.5mm (0.25in) **Protrusion** 

**PMK** 7.4W

## Bowers & Wilkins

www.bowers-wilkins.com

Nautilus, Flowport and FST are trademarks of B&W Group Ltd.
Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE

