Bowers & Wilkins

Custom Installation CCM Cinema 7



See nothing, hear everything

This speaker is designed for down-firing, in-ceiling left, center and right speaker positions in a discreet home cinema system. Both drivers are angled to the mounting surface and can be directed towards listeners so they hear the correct balance of sound. That way, dialogue is crystal clear and special effects come across accurately.

Thanks to Bowers & Wilkins unique QuickDogs™ fixing method, installation is simple, requiring no tools. And, in common with other recent CI products, it features an ultra-narrow bezel and magnetically attached metal grille, both of which can be customised to complement décor.

If preferred, the supplied round grille can be replaced with an optional, square CCM683 grille.



Technical Specifications

Description 2-way in-ceiling system

Drive Units 1x Ø25mm (1 in) Nautilus[™]

swirl loaded aluminium dome tweeter 1x Ø180mm (7 in) blue Kevlar®

cone bass/midrange

Frequency range (-6dB) 45Hz – 50kHz

Recommended 25W – 150W Amplifier Power

Sensitivity 88dB (2.83V, 1m)

Nominal Impedance 8Ω (4.5 Ω minimum)

Frame diameter 290mm (11.4 in)

Cut-out diameter 249mm (9.8 in)

Depth behind surface 114.3mm (4.5 in) (.5 in minimum wall)

Pre-mount Kit PMK C8

Back Box BB 6C

Square Grille Option GR68SQ

Packed 1 per carton

Bowers & Wilkins

www.bowers-wilkins.com

Nautilus and QuickDogs are trademarks of B&W Group Ltd.

Kevlar is a trademark of DuPont

Copyright © B&W Group Ltd. E&OE

